

INDUSTRIAL LUBRICANTS

Solutions



CUT™

CUTTING, LUBRICATING AND COOLING FLUID

- Contains lubricating and cooling agents
- Reduces friction
- Perfect for cutting tools and material



Slaters®
Since 1911

CARE FOR WORK ENVIRONMENTS®

CUT™

CUTTING, LUBRICATING AND COOLING FLUID

MULTI-PURPOSE

State CUT is specifically designed to lubricate, cool and protect tools and materials used in all cutting, threading, tapping and drilling operations.

PROTECTS AND PRESERVES

State CUT contains special inhibitors to protect against rust and corrosion. The unique combination of coolants and lubricants reduces friction and disperses heat build-up. This action provides cleaner, smoother cuts. Cutting edges remain sharp longer and helps to extend tool life.

VERSATILE

Reinforced cutting compound is ideal for steel, stainless steel, aluminum, brass, copper, nickel, monel, spring steel, chrome steel and other metals. Do not use on beryllium, titanium or tantalum.

ECONOMICAL, REDUCES WASTE

State CUT is specially formulated to eliminate spillage, dripping, evaporation and runoff. State CUT stays where it's sprayed. The jet stream spray reduces splash and permits State CUT to be sprayed where it's needed. This eliminates costly overspray.

APPLICATIONS

- Boring
- Honing
- Drilling
- Reaming
- Gear Grinding
- Broaching Operations
- Gear Hobbing and Shaping
- Matching
- Milling
- Planning
- Profiling
- Tapping
- Threading

TECHNICAL DATA:

APPEARANCE: aerosol foam spray

COLOR: brown

ODOR: mild petroleum

PROPELLANT: does not contain Chlorofluorocarbons

SHELF LIFE: minimum one year

SPECIFIC GRAVITY: 0.92

COLD STABILITY: 0°F

PACKAGING

121178-12 16 OZ Aerosol/CS12
121178-24 16 OZ Aerosol/CS24



State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada
6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico
Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, P.R. 00962
To Order Call: 787-275-3185

